



LIFT-A-LOFT

SPX MAINTENANCE PLATFORM

SPX MAINTENANCE PLATFORM



PLATFORM DATA (AVERAGE)

Travel Speed (Variable & Controllable)

- High Speed – 2.4 mph (3.9 km/hr)
- Elevated – 0.68 mph (1.13km/hr)
- Gradeability – 10%
- Telescoping Scissor Design Provides Maximum Stability at Full Elevation
- Maximum Platform Height - 32' (9.75m)
Minimum Platform Height - 4'5" (1.34m)
- Platform Lift Speed – 0.42 ft/sec (0.13 m/sec)
- Platform Lower Speed – 0.63 ft/sec (0.19 m/sec)
- Main Platform Capacity 3,000 lbs (1,360.8 kg)
- Extenda-deck Capacity 1,000 lbs (453.6 kg)

OPTIONS

- 6', 8, or 10' (1.83, 2.44, or 3.05m) Power Deck Extension (Extenda-Deck)
- All Motion Alarm
- Flashing or Rotating Light
- 36VDC Power
- Gasoline Engine
- Diesel Engine
- Split "V" Deck Design
- Padded Rails
- Adjustable Work Lights
- Extreme Cold Weather Package
- Contact LIFT-A-LOFT for Custom Designs
- Pressure sensitive trip Bumpers

SAFETY

- Brakes Spring Applied, Pressure Released
- Deadman Controls
- Anti-slip Work Surface
- Holding Valves on Lift Cylinders
- Emergency Stop Switch (all control stations)
- Lanyard Attachments
- Aircraft Bumpers
- Ceestrered Stabilizers